





# **CITIMAX D Series**



Citimax D series is the new generation of truck refrigeration unit with decades of Carrier's practice and R&D experience. More than ever, today's CITIMAX D series not only is a more powerful and reliable unit but also can provide customers a faster, lighter, smarter and more efficient usage benefit.



### The New Controller—Intelliting Let Intelligence Be Seen

- · 3.2" large screen
- · Chinese/English display
- · Upgraded control logic
- · Data storage & download
- · LYNX service as an option



## **More Reliable Performance**

- Larger cooling & heating capacity
- Up to 22% pre-cooling speed improvement



#### **Lighter & More Compact**

- Up to 26% lighter given by a more compact design
- More loading ability & easier installation





- \*\*12000 hours long-life fans
- Better installation quality thanks to upgraded compressor with pre-assembled fittings





#### **Ultra-thin Evaporator**

- Less impact of cargo stacking given by newly inclined-evaporator design
- Larger air flow & more loading space



#### **More Efficient & Sustainable**

- Up to 38% of less refrigerant usage
- Better efficiency & environment friendly



- \*All the above are compared with legacy Citimax.

  \*\*Data from lab test. Real service lifetime will have difference based on real usage situation.

Model	Cooling Capacity(W)		Heating Capacity(W)		Condenser Dimensions	Evaporator Dimensions	Weight	Refrigerant	Voltage	Current	Compressor
	0°C/+30°C	-20°C/+30°C	+18°C/-18°C	(m³/h)	(W*H*D mm)	(W*H*D mm)	(KG)	(R404A,KG)	(V)	(A)	Model
CITIMAX D5	5300	2700	4400	2200	1314*304*389	1106*238*603	59	2.0	12/24	30/18	Carrier160
CITIMAX D6	6000	3100	4600	2200	1314*304*389	1106*238*603	62	2.2	12/24	34/19	Carrier160
CITIMAX D7	7100	3700	5600	2500	1479*312*389	1304*217*698	69	2.5	12/24	50/30	Carrier210

**Carrier Transicold** China Headquarter: No.1235 Yecheng Rd,

Jiading District, Shanghai-201821 Phone: (86-21) 59166868 Shanghai Service Center: Building A,No.4800,

Baoqian Rd, Jiading District, Shanghai-201806 Phone: (86-21) 57821379 Fax: (86-21) 57821375



